

Lafferty Spray-Alls™

Low Pressure
Models for 35 to 100 PSI Water Pressure



Lafferty Low Pressure Spray-Alls™ efficiently apply detergent, sanitizer or any other chemical to any surface and operate with available water pressures in the ranges of 35 to 100 PSI. Three models are available each with a different water flow rate.

SPRAY-ALL FLOW CHART			WATER PRESSURE IN POUNDS PER SQUARE INCH (PSI)						
			40 PSI	50 PSI	60 PSI	70 PSI	80 PSI	90 PSI	100 PSI
Model	Nozzle	Hose Size	SPRAY-ALL WATER FLOW RATE (GPM)						
W-10	2510	½"	0.41	0.44	0.45	0.49	0.50	0.53	0.56
W-20	2520	½"	0.84	0.91	1.00	1.12	1.15	1.19	1.22
W-50	2550	½"	2.10	2.28	2.49	2.67	2.80	3.00	3.20

Features And Benefits

- Stainless steel (SS) base with hinged cover
- Polypropylene (PP) injector body
- Metering tips
- 50' hose assembly with 14" PP wand and a SS steel fan nozzle.

Options

- Stainless Steel Hose Rack
- 1 Gallon Stainless Steel Jug Rack (round or square)
- 2½ Gallon Stainless Steel Jug Rack (inside dimensions 8½" x 10½")
- 5 Gallon Stainless Steel Jug Rack (inside dimensions 12" x 12")

Models:

- W-10 Spray-All 970210
- W-20 Spray-All 970220
- W-25 Spray-All 970225
- W-50 Spray-All 970250

Requirements:

- 35 – 100 PSI Water — Up to 5 GPM
- 1/2" I. D. Discharge Hose
- Ambient to 140° F



5614 Oak Grove Road
 North Little Rock, Arkansas 72118
 (501) 851-2820 or 1-800-999-2820

www.laffertyequipment.com

Performance You Can Trust!

