

Acid Spray-Alls & Airless Foamers



Mixing Stations



Sprayers



Foamers



Asphalt Release



Portables



Lafferty Acid Spray-Alls and Airless Foamers are designed for use with highly corrosive chemicals like those used in concrete removal and aluminum brightening. Lafferty Acid Spray-Alls and Airless Foamers draw chemical concentrate directly from original shipping containers, reducing employee exposure to chemicals. Twenty color-coded metering tips provide consistent dilution ratios.

Lafferty Acid Spray-Alls produce a uniform spray for even coverage. These models provide up to a 3.2-to-1 dilution ratio.

Lafferty Airless Foamers produce wet, clinging foam without compressed air. These models provide up to a 4-to-1 dilution ratio.

Features And Benefits

- Venturi action
- Metering tips
- Polypropylene base and cover
- Polypropylene injector body
- Spray-Alls - 50' discharge hose assembly with PVC ball valve, 28" PP extension wand, polypropylene nozzle protector, and PVDF nozzle or polypropylene airless foam wand.

Apply up to three different chemicals, depending on the model.

| Model # | Description |
|---------|-------------------------------|
| 972011 | 1-Way Spray-All Complete |
| 972012 | 2-Way Spray-All Complete |
| 972013 | 3-Way Spray-All Complete |
| 972211 | 1-Way Airless Foamer Complete |
| 972212 | 2-Way Airless Foamer Complete |
| 972213 | 3-Way Airless Foamer Complete |

Requirements / Specifications

| | | |
|-----------------|---------------------|----------------------|
| Water Pressure | 40 - 150 psi | 2.8 - 10.3 bar |
| Water Flow Rate | @ 40 psi 1.3 gpm | @ 2.8 bar 4.9 lpm |

| | | |
|----------------|---------|---------|
| Discharge Hose | | |
| ID | 1/2 in. | 12.7 mm |
| Length | 50 ft. | 15.2 m |

- Compressed air



North Little Rock, Arkansas
(501) 851-2820 or 1-800-999-2820