

Drum Bung Mount LCSS Foamer

MODEL # 915615

OVERVIEW

The Drum Bung Mount LCSS Foamer is a drum-mounted, medium volume foam applicator for projecting foaming chemicals on to any surface up close or at a distance. This stainless steel venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate directly from the drum into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 12 feet.

Key Features

- Screws into, and dispenses directly from, chemical concentrate drums for increased efficiency
- Equipped with both fine and coarse threads
- Machined stainless steel foamer body for maximum chemical and temperature resistance
- Designed for foam cleaning medium to large surfaces
- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available as a wall-mounted unit (#915105)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- Machined stainless steel foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- Hatchery
- Industrial
- Metal Processing
- Military
- Paper Mill
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 180°F
Pressure	35 to 125 PSI
Flow	1.34 GPM @ 40 PSI
Supply Line	1/2"

Compressed Air

up to 3 CFM

Hose

3/4" ID x 40'

Nozzle

50250

Dilution Ratio Range

306:1 to 6:1 @ 40 PSI