

# Portable 60 Gallon Super HV Foamer

MODEL # 916960

## OVERVIEW

The Portable 60 Gallon Super HV Foamer is a very high volume foam applicator featuring a 4-wheel, all stainless steel cart assembly with a 60 gallon chemical concentrate tank. This venturi injection system uses city water pressure (30 - 150 PSI) to draw and blend chemical concentrate from the tank into the water stream to create an accurately diluted solution. An incredible amount of rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and foam nozzle on to large surfaces and high ceilings at distances up to 45 feet.

## Key Features

- Projects a very high volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- 60 gallon chemical concentrate tank reduces downtime for refilling trips to the chemical room
- Open flow foam nozzle projects foam up to 45' for cleaning very large areas, equipment and high ceilings without ladders or lifts
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available as a wall-mounted unit (#916250)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

## Includes

- All stainless steel 4-wheel cart with non-marking tires
- Heavy-duty, stainless steel swivel casters
- 60 gallon heavy-duty, wide-mouth chemical concentrate tank
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, stainless steel foam nozzle

## APPLICATIONS

- Large Area Foam Cleaning
- Food & Beverage
- Industrial
- Metal Processing
- Military
- Odor Control
- Paper Mill
- And Many Other Applications!



## REQUIREMENTS

### Chemical Concentrate

#### Water

Temperature	up to 160°F
Pressure	30 to 150 PSI
Flow	9.8 GPM @ 40 PSI
Supply Line	3/4"

#### Compressed Air

up to 12 CFM

#### Hose

1-1/2" ID x 50'

#### Nozzle

Super HV Open Flow Wand

#### Dilution Ratio Range

2,240:1 to 10:1 @ 40 PSI