

MODEL # 917115DU

OVERVIEW

The Hyper SSDU Foamer is a 3.3 GPM @ 700 PSI foam applicator for simultaneously projecting 2 foaming chemicals on to any surface up close or at a distance. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend 2 chemical concentrates into the water stream at the same time to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the foam hose, wand and fan nozzle at distances up to 13 feet.



- Simultaneously blends 2 chemicals into the water stream
- Stainless steel foamer body for maximum durability and chemical resistance
- Projects a substantial volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 1.5 minutes
- Optional zero degree nozzle for increased foam throw
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available for a single chemical (#917115)
- See other high water pressure applicators in Catalog 3

Includes

- Stainless steel mounting bracket
- Machined stainless steel foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with open flow polypropylene foam wand and fan nozzle



Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square# 224200Jug Rack, SS, 2 1/2 Gallon# 224210Jug Rack, SS, 5 Gallon, Round/Square# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Optional Zero Degree Nozzle (For Increased Range)

Nozzle, NPB, 3/4" - 00400 # 180154

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315 Check Valve, Air, SS/Viton, 1/4" # 491306

REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 180°F

 Pressure
 400 to 1000 PSI

 Flow
 3.3 GPM @ 700 PSI

Supply Line 3/8

Compressed Air up to 5 CFM Hose 3/4" ID x 50'

Nozzle 65300

Dilution Ratio Range 756:1 to 8:1 @ 700 PSI



- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Industrial
- Metal Processing
- And Many Other Applications!











