Model 25 Compact Airless Foamer (No Gun)

MODEL # 969923-B32

OVERVIEW

The Model 25 Compact Airless Foamer is a unique medium volume hose-end foam gun for diluting and applying foaming chemicals to any surface up close or at distances up to 12 feet. This unit uses standard city water pressure to draw chemical concentrate from the attached bottle and blend it into the water stream. The accurately diluted solution flows through the foam wand to create a clinging, wet foam. This handy foamer is offered without a trigger gun and can be used in conjunction with the gun on another compact unit. Use it with a Compact Sprayer to easily switch between foam, rinse and spray.

Key Features

- Attaches to the trigger gun from another Lafferty compact sprayer or foamer
- Allows the user to easily switch chemicals or to use in conjunction with a Compact Sprayer to create a foam/rinse/spray cleaning system
- Creates rich, wet foam which increases chemical contact time and effectiveness
- Foam provides visual confirmation of complete coverage
- Projects foam up to 12' (depending on water pressure)
- Durable! Foamer body is machined in the USA, not molded
- Outlasts and outperforms similar molded plastic products
- With less than half the flow rate of competing models, you save money
- Light, 32 oz bottle reduces wrist and arm fatigue and the risk of repetitive strain injuries
- No moving parts! Venturi action dilutes chemical consistently with precision metering tips
- Great performance with water pressure as low as 20 PSI
- Color-coded lids help identify equipment and chemicals to enhance user safety (*blue standard red, yellow, or green optional*)
- Similar model available with a lower flow rate (#969918-B32)
- Available with a trigger gun (#969925-B32)
- See more Lafferty chemical applicators in Catalog 11

Includes

- Machined polypropylene foamer body
- 32 oz wide-mouth, polyethylene bottle
- 20 color-coded precision metering tips to set dilution ratios
- Quick disconnect plug

OPTIONS

Additional Bottles	
Bottle, 32oz (Includes Solid Lid)	# 709082
Unit Storage Rack	
Compact Foamer/Sprayer Rack, Stainless Steel	# 224301
Quick Disconnect Socket	
QD, SS, Socket FGH	# 350474SS



REQUIREMENTS

Chemical Concentrate

Water	
Temperature	up to 160°F
Pressure	20 - 100 PSI
Flow	1.25 GPM @ 40 PSI
Supply Line	1/2"
Dilution Ratio Range	286:1 to 6:1 @ 40 PSI

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

