# **Portable PD- Precision Foamer**

MODEL # 935165

## **OVERVIEW**

The Portable PD Precision Foamer is a low volume foam applicator that is ideal for jobs where precision application and tight control of overspray are required such as for cleaning restaurant hoods and vents. This unit features an all stainless steel cart assembly and on-board 120V air-compressor. An air-operated, double-diaphragm FloJet Pump draws ready-to-use chemical from a user-supplied pail and injects compressed air to create rich, clinging foam which greatly increases volume and coverage ability. The foam is then projected through the discharge hose, trigger gun and fan nozzle.

### **Key Features**

- Projects a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- · Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Draws ready-to-use chemical solution
- Adjustable foam consistency (wet/dry)
- An on-board, quiet, 120V compressor drives the pump
- · Chemical resistant wetted components ensure durability and years of reliable service
- Available as wall-mounted unit (#935155)

• See other air-operated foamers and sprayers in Catalog 4

#### Includes

- All stainless steel 4-wheel cart, locking enclosure and integrated stainless steel hose rack
- Non-marking tires & stainless steel swivel casters
- Stainless steel, round, 5 gallon jug rack (square optional)
- 120V air compressor
- FloJet 1/4" AODD pump (Santoprene diaphragms)
- · Air inlet ball valve
- Stainless steel precision foamer body
- 50' discharge hose and polypropylene trigger gun, wand with stainless steel nozzle

## **OPTIONS**

#### **5 Gallon Pail**

Pail, 5 Gallon Round W/ Suction Stem # 709105

Square Jug Rack Conversion Specify Round or Square Jug Racks at time of order

Alternate Seal Materials - Santoprene Standard	
Viton Upgrade: Flojet Air Pump & Check Valves	# 710756
Kalrez Upgrade: Flojet Air Pump & Check Valves	# 710755

Alternate Air Check Valve - EPDM Standard Check Valve, Air, SS, 1/4" MM (Viton / Hast)

**APPLICATIONS** 

- Hood & Vent Cleaning
- Restaurants
- Vehicle Wash
- Food & Beverage
- Janitorial/Sanitation
- Supermarkets
- And Many Other Applications!



## REQUIREMENTS

Ready-to-Use Chemical Solution	
Solution Temperature	120°F MAX
Electric	120V - Min.15 AMP Circuit

# 491306

