633 8-Way Fogger

MODEL # 950008

OVERVIEW

The 633 8-Way Fogger is a damp mist sprayer that uses compressed air (30 CFM @ 80 PSI) and venturi action to draw ready-to-use chemical solution from a nearby container and project it up to 15 feet in 8 directions. The adjustable output sprays mist (fog) into the air to cover exposed surfaces and penetrate hard-to-reach areas.

Key Features

- Atomizes and sprays chemical solutions using only compressed air.
- Venturi action draws pre-diluted chemical from a nearby container
- Projects up to 15' in 8 directions
- Damp fog (mist) fills the air and covers exposed surfaces with chemical, including hard-to-reach areas
- Optional needle valve can reduce chemical usage and output wetness
- Chemical pickup can be installed on the top or bottom
- Chemical resistant polypropylene construction ensures durability and years of outstanding performance
- See Catalog 7 for hand held, permanently mounted and portable foggers
- Use the Lafferty Fogger Planning Tool to design the optimal fogging system for any facility

Includes

- Machined polypropylene fogger body
- Metering tip holder
- 10' chemical suction tube and strainer

OPTIONS

Stainless Steel Jug Racks

| 1 Gallon Round/Square | # 224200 |
|---|------------|
| 1 Gallon Round/Square Locking | # 224200-L |
| 2 ½ Gallon (8 ½" x 10 ½") | # 224210 |
| 5 Gallon Round/Square Locking (12" x 12") | # 224214 |
| 5 Gallon Round/Square (12" x 12") | # 224215 |

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

To Control Solution Flow (Wetness of Fog)

Needle Valve, PVC, 1/4" FM # 660781

APPLICATIONS

- Sanitizers
- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Military
- Odor Control
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Ready-to-Use Chemical Solution

Temperature up to 160°F Pressure 20 to 35 PSI

Compressed Air up to 30 CFM @ 80 PSI

Minimum Air Supply Line 1/2"



