

Multi-Pet Washing System

MODEL # 975974

OVERVIEW

The Multi-Pet Washing System is a combination system for diluting and projecting up to 4 chemicals as airless foam or spray and then rinsing. This system is ideal for bathing pets in professional grooming shops, but has countless potential applications. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Project wet, clinging foam using the airless foam wands or use the fan nozzles to project a chemical spray with just the right amount of pressure. Select low or high flow settings for small or large jobs.

Key Features:

- Applies any 4 liquid chemicals as wet, clinging foam with the foam nozzles or attach the spray nozzles to project the solution in a fan pattern spray
- Use 4 different chemicals or different concentrations
- Rinses at full pressure
- Low flow and high flow options let you choose the right amount of water and chemical for each job (2 low flow, 2 high flow chemical pickups)
- Works with all brands of chemicals so you are not restricted to expensive name brands
- Draws chemical concentrate from any container
- Water pressure gauge eliminates guessing, reduces set-up time, and helps with troubleshooting
- Chemical resistant wetted components ensure reliable performance for years with minimal maintenance

Includes:

- 10' water supply hose
- Machined polypropylene injector assembly
- Easy-to-read pressure gauge for incoming water
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose (can be cut to length)
- Garden hose gun
- Low & high volume airless foam wand
- Low & high volume spray nozzles

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack	# 224150
Small Stainless Steel Hose Rack	# 224145

Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer	# 709101
---------------------------------	----------

For Quickly Changing Hose-End Applicators

QD, NPB, Plug MGH	# 350472
QD, SS, Socket FGH	# 350474SS

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4"	# 491315
---------------------------------------	----------

APPLICATIONS

- Professional Pet Grooming
- Equine Bathing
- Stables/Wash Bays
- Auto Detail Shops
- And Many Other Applications!



REQUIREMENTS

Water

Temperature	up to 160°F
Pressure	35-125 PSI

Flow

Low	0.4 GPM @ 40 PSI
High	1.34 GPM @ 40 PSI
Rinse	4.0 GPM @ 40 PSI

Hose

	1/2" ID
--	---------

Nozzle

Low Flow Foam	Bullet Airless Foam Wand
High Flow Foam	A-25 Airless Foam Wand
Rinse	Trigger Gun
Low Flow Spray / Rinse	2510
High Flow Spray / Rinse	4040

Dilution Ratio Range @ 40 PSI

Low Flow	91:1 to 8:1
High Flow	306:1 to 6:1