WR-2 Foam / Rinse / Foam With Pistol Grip Gun Kit

MODEL # 975224











OVERVIEW

The WR-2 Foam/Rinse/Foam System is a combination applicator with a rinse mode. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. The foaming solution then flows through the discharge hose to the airless foam wand which draws in atmospheric air to create and project wet, clinging foam on to any surface up close or at distances up to 6 feet. Quick connect the pistol grip gun to rinse at full pressure.

Key Features

- Designed for foam cleaning, rinsing and foam sanitizing medium to large sized areas where compressed air is not available
- Projects wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Quick connect the pistol grip gun to rinse at full pressure as a fan pattern spray
- Chemical resistant components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Water pressure gauge eliminates guessing, reduces set-up time, and helps with troubleshooting
- See other Foam/Rinse/Spray systems in Catalog 1

Includes

- Machined polypropylene manifold and injector body
- Easy-to-read pressure gauge for incoming water
- Ball valves to alternate foaming, rinsing and foam sanitizing
- 20 color-coded precision metering tips to set dilution ratios
- 50' hose and discharge assembly
- Quick connect machined polypropylene airless foam wand
- Quick connect insulated pistol grip gun with fan nozzle and nozzle protector



OPTIONS

Stainless Steel Hose Racks	
Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon, Round/Square	# 224215
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101
Alternate Check Valve - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315

APPLICATIONS

- Supermarkets
- Deli's
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Any Foam/Rinse/Sanitize Application!

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	4 GPM @ 40 PSI
Supply Line	1/2"
Hose	
Foam	1/2" ID x 50'
Rinse	1/2" ID x 50'
Foam	1/2" ID x 50'
Nozzle	
Foam	A-25 Airless Foam Wand
Rinse	2550
Foam	A-25 Airless Foam Wand
Dilution Ratio Range @ 40 PSI	
Foam	306:1 to 6:1
Foam	306:1 to 6:1

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com