HVHC Foamer

MODEL # 916115-G

OVERVIEW

The HVHC Foamer is a high volume, "high concentrate" foam applicator that will produce strong dilution ratios for the toughest cleaning jobs. Weaker dilution ratios are achieved with metering tips. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend a high concentration of chemical concentrate into the water stream to create a very strong chemical solution. A high volume of rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 15 feet (25 feet with zero degree nozzle). Gauges display incoming water and air pressure.

Key Features

- Achieves strong chemical concentrations up to 2.8 to 1
- Weaker dilution ratios controlled by precision metering tips
- Designed for foam cleaning large areas and equipment
- Projects a high volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for fast coverage (up to 15' range)
- Zero degree nozzle for up to 25' range
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available for standard dilution ratios (#916105-G)
- See other configurations of Lafferty city water pressure foamers in Catalog 1

Includes

- · Stainless steel mounting bracket
- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with stainless steel discharge ball valve
- Polypropylene foam wand with fan and zero degree nozzles

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

2 ½ Gal. (8 ½" x 10 ½") # 224210 5 Gallon (12" x 12") Round/Square # 224215

Drum & Tote Stick Lengths & Seal Materials

 Drum Stick, 33" (Viton or EPDM)
 # 491643 / 491643-E

 Drum Stick, 48" (Viton or EPDM)
 # 491648 / 491648-E

 Drum Stick, 54" (Viton or EPDM)
 # 491645 / 491653-E

 Tote Stick, 33" (Viton or EPDM)
 # 491654 / 491654-E

 Tote Stick, 48" (Viton or EPDM)
 # 491656 / 491656-E

APPLICATIONS

- Agriculture/Horticulture
- Vehicle Wash
- Food & Beverage
- Industrial
- Military
- Paper Mill



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 3.5 GPM @ 50 PSI

Supply Line 3/4"

 Compressed Air
 up to 5 CFM

 Hose
 1" ID x 50'

 Nozzle
 00400 or 50400

Dilution Ratio Range 720:1 to 3:1 @ 40 PSI

