

MODEL # 989312

OVERVIEW

The Level Master™ with Stainless Steel, Horizontal Mounted Bracket is a water driven chemical proportioner that bolts to the top of user-supplied tank and automatically maintains a constant supply of ready-to-use solution. When the solution in the tank drops below a pre-set level, this venturi injection system uses city water pressure (25 - 80 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution using precision metering tips. The solution replenishes at 2.4 GPM @ 40 PSI and cycles continuously. A secondary fail-safe float prevents overfilling.



- Stainless steel, horizontal mount bracket bolts to the top of a user-supplied tank
- Automatically maintains a pre-set level of ready-to-use chemical solution
- Dual magnetic float valve design includes a primary valve to regulate normal operation and a secondary fail-safe valve to shut off the system if the primary float valve malfunctions
- Unsinkable solid polypropylene floats suspended by rigid "push rods" ensure smooth operation and prevent the float valves from sticking in the open position
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Downstream check valve prevents back-flow of liquid or vapor into the float valves to eliminate the potential for damage to internal mechanisms
- Industrial-strength design holds up in tough environments
- Available with a mounting clamp (#989308)
- Available to dilute and blend 2 chemicals (#989324)
- See all of our Level Master™ configurations and other Lafferty chemical management systems in Catalog 9

Includes

- Stainless steel mounting bracket with bolt holes (mounting bolts not included)
- · Water supply inlet strainer
- Water supply shut-off ball valve
- Machined polypropylene injector body
- 2 magnetic float valves (primary and fail-safe) with solid polypropylene floats suspended by rigid CPVC push rods
- Stainless steel / Viton back-flow prevention check valve
- 20 color-coded metering tips to set dilution ratios

OPTIONS

Alternate Chemical Check Valve - Viton Standard

Check Valve, Chemical, PP(W), 1/4" (EPDM)

491401

Drum & Tote Sticks Available

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

 $\begin{array}{lll} \mbox{Temperature} & \mbox{up to } 160\mbox{°F} \\ \mbox{Pressure} & 25\mbox{ to } 80\mbox{ PSI} \\ \mbox{Flow} & 2.4\mbox{ GPM @ 40\mbox{ PSI}} \\ \end{array}$

Supply Line 1/2

Dilution Ratio Range 549:1 to 2:1 @ 40 PSI

