

2-Way 207HC Filling Station

MODEL # 980008

OVERVIEW

The 2-Way 207HC Filling Station has a water flow rate of 2 GPM @ 40 PSI and is a "high concentrate" 2-chemical proportioner for filling any sized containers with strong solutions using a trigger gun. This venturi injection system uses city water pressure (40 - 80 PSI) to draw and blend a high concentration of chemical into the water stream to create up to 1:1 dilution ratios.

Key Features

- Achieves strong dilution ratios, up to 1:1 (with water thin chemicals)
- Weaker ratios are controlled by precision metering tips
- Designed to apply 2 different chemicals or 2 different concentrations on the same chemical
- Water flow rate of 2 GPM @ 40 PSI for filling any sized container or equipment
- Eliminates manual mixing and optimizes chemical utilization, employee safety and labor efficiency
- Dispenses through a trigger gun to prevent the unit from running unattended
- Extended length hose to fill large equipment at a distance
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Draws chemical concentrate from any sized container
- Available with a lower flow rate (#980006)
- See other chemical management systems in [Catalog 9](#)

Includes

- Stainless steel mounting bracket
- Stainless steel inlet ball valve
- Machined polypropylene injector body
- Chemical ball valves
- 20 color-coded precision metering tips to set dilution ratios
- 15' discharge hose
- Polypropylene trigger gun with stainless steel and Viton internal components

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - Viton Standard

Check Valve, Chemical, PP, 1/2" HB (EPDM) # 491403

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Military
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 40 to 80 PSI
Flow 2.0 GPM @ 40 PSI
Supply Line 1/2"

Hose

3/4" ID x 15'

Nozzle

Trigger Gun

Dilution Ratio Range

457:1 to 1:1 @ 40 PSI