

Uni-Body 2-Way Foamer

MODEL # 975557-G

OVERVIEW

The 2-Way Uni-Body Foamer is a medium volume foam applicator (1.3 GPM @ 40 PSI) for projecting up to 2 foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrates into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through a fan nozzle at distances up to 12 feet. Use the chemical ball valves to inject the 2 chemicals separately or simultaneously. Gauges display incoming water and air pressure.

Key Features

- The unique machined polypropylene uni-body design is both compact and cost-effective
- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Designed to apply 2 separate chemicals or 2 different concentrations of the same chemical
- Chemicals can be applied separately or simultaneously by adjusting the ball valves
- Designed for foam cleaning medium to large surfaces
- Fan pattern nozzle for quick coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Available for only 1 chemical (#975555-G)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- 2 chemical ball valves
- 20 color-coded metering tips to set dilution ratios
- 40' discharge hose, stainless steel ball valve, polypropylene foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

1 Gallon Round/Square # 224200

1 Gallon Round/Square Locking # 224200-L

2 ½ Gallon (8 ½" x 10 ½") # 224210

5 Gallon Round/Square Locking (12" x 12") # 224214

5 Gallon Round/Square (12" x 12") # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Industrial
- Military
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 1.34 GPM @ 40 PSI
Supply Line 1/2"

Compressed Air

up to 3 CFM

Hose

3/4" ID x 40'

Nozzle

50250

Dilution Ratio Range

306:1 to 6:1 @ 40 PSI