Model 15 Compact Airless Foamer

MODEL # 969920-B32

OVERVIEW

The Model 15 Compact Airless Foamer is a unique low volume hose-end foam gun for diluting and applying foaming chemicals to any surface. This unit uses standard city water pressure to draw chemical concentrate from the attached bottle and blend it into the water stream. The accurately diluted solution flows through the foam wand to create a clinging, wet foam which is then projected on to any surface up close or at distances up to 7 feet. Quick disconnect the chemical assembly to rinse.



- · Creates rich, wet foam which increases chemical contact time and effectiveness.
- Foam provides visual confirmation of complete coverage
- Projects foam up to 7' (depending on water pressure)
- Durable! Foamer body is machined in the USA, not molded
- Outlasts and outperforms similar molded plastic products
- The stainless steel quick disconnect socket features 6 retaining balls to lock the bottle and foam assembly securely in place
- Ouick disconnect the foam assembly to rinse
- With less than half the flow rate of competing models, you save
- · Light, 32 oz bottle reduces wrist and arm fatigue and the risk of repetitive strain injuries
- No moving parts! Venturi action dilutes chemical consistently
- Great performance with water pressure as low as 20 PSI
- · Color-coded lids help identify equipment and chemicals to enhance user safety
- · Available without the gun for quickly changing chemicals or equipment on the job (#969920-B32)
- Available with a higher flow rate (#969925-B32)
- Compact units are also offered as sprayers
- See more Lafferty chemical applicators in Catalog 11

- Machined polypropylene foamer body
- · Quick disconnect plug & 6-ball socket
- 32 oz wide-mouth, polyethylene bottle
- 20 color-coded metering tips for setting dilution ratios
- · Garden hose gun with inlet screen/filter

OPTIONS

Additional Bottles

Bottle, 32oz (Includes Solid Lid) # 709082

Unit Storage Rack

Compact Foamer/Sprayer Rack, Stainless Steel # 224301

Adapter for Wider Close-Range Foaming

Compact Foamer Spreader Nozzle # 180325





REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F Pressure 20 to 100 PSI Flow 0.7 GPM @ 40 PSI

Supply Line

Dilution Ratio Range 160:1 to 6:1 @ 40 PSI

APPLICATIONS

- · Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



