

WR-1 Foam / Rinse With Pistol Grip Gun Kit

MODEL # 975127

OVERVIEW

The WR-1 Foam / Rinse System is a combination medium volume airless foam applicator with a rinse mode. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. The solution then flows through the discharge hose to the airless foam wand which draws in atmospheric air to create and project wet, clinging foam on to any surface up close or at distances up to 6 feet. Quick connect the pistol grip gun to rinse at full pressure.

Key Features

- Foam and Rinse with one convenient system
- Designed for foam cleaning and rinsing medium to large sized areas where compressed air is not available
- Projects wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Quick connect the pistol grip gun to rinse at full pressure
- Chemical resistant components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Water pressure gauge eliminates guessing, reduces set-up time, and helps with troubleshooting
- Available with a Sanitize function (#975227)
- See other Foam/Rinse/Spray systems in [Catalog 1](#)

Includes

- Machined polypropylene manifold and injector body
- Easy-to-read pressure gauge for incoming water
- Ball valves to alternate between foaming and rinsing
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose and quick connect ball valve
- Quick connect polypropylene airless foam wand
- Quick connect insulated pistol grip gun with fan nozzle and nozzle protector

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Supermarkets
- Deli's
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Any Wash/Rinse Application!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 4 GPM @ 40 PSI
Supply Line 1/2"

Hose

Foam 1/2" ID x 50'
Rinse 1/2" ID x 50'

Nozzle

Foam A-25 Airless Foam Wand
Rinse 2550

Dilution Ratio Range @ 40 PSI

Foam 306:1 to 6:1

Lafferty
EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES

1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com