RADAR™ EP-LM Spray System

MODEL # 977890

OVERVIEW

The RADAR™ EP-LM Spray System is an electric eye activated, asphalt release applicator that mounts to a user-supplied drivethough arch for spraying asphalt truck beds. This system uses an electric pump to draw ready-to-use chemical solution from the included 7 Gallon Level Master™ tank which maintains a constant supply of solution. When a truck breaks the electric eye's lineof-sight, a delay timer allows the driver to position the truck under the spray nozzle before spraying begins and a run timer applies release agent for a pre-set time or until the vehicle leaves the spraying area, whichever is first.

Key Features

- Designed to spray asphalt release chemicals on to truck beds from a nozzle that attaches to an existing drive-through spray bar
- The electric pump draws ready-to-use chemical solution from the 7 Gallon Level Master™ which automatically maintains a constant supply of solution
- The system delays for an adjustable length of time when a truck breaks the beam of the electric eye, allowing the driver to position the truck, before activating for an adjustable, pre-set length of time
- The driver remains in his cab and avoids the risk of slip-and-fall injury and chemical waste
- Evenly coats the truck bed in just seconds, reducing run-off and chemical waste
- · Spraying will stop if th
- The Level Master[™] ad using city water press
- Chemical resistant wetted compared and the second se outstanding performance with minimal maintenance
- chemical applicators in Catalog 8

- Lockable, stainless steel pump enclosure
- 110V stainless steel electric pump
- Control box with delay/run timers and electric eye set
- 7 Gallon Level Master[™] system
- 40' discharge hose with custom fan spray nozzle

OPTIONS


Heater Assembly

Retro-Fit Heater Assembly

Drum & Tote Stick Lengths & Seal Materials

Drum Stick, 33" (Viton or EPDM) Drum Stick, 48" (Viton or EPDM) Drum Stick, 54" (Viton or EPDM) Tote Stick, 33" (Viton or EPDM) Tote Stick, 48" (Viton or EPDM) Tote Stick, 54" (Viton or EPDM)







REQUIREMENTS

Chemical Concentrate

Water	
Temperature	up to 160°F
Pressure	35 to 125 PSI
Supply Line	1/2"
Hose	3/4" ID x 40'
Nozzle	#180193SS
Electric	120V / 20A
See Separate Instructions for:	
Level Master™	989304





e driver leaves the area early
chieves a wide range of dilution ratios
ure and precision metering tips
etted components ensure years of

- Available with a magnetic sensor (#977895)
- · See other Lafferty asphalt release equipment and industrial

Includes



720981