HPDU Foamer

MODEL # 918105DU

OVERVIEW

The HPDU Foamer is a 2 GPM @ 700 PSI foam applicator for simultaneously applying 2 foaming chemicals to any surface up close or at a distance. This venturi injection system uses high water pressure (400 - 700 PSI) to draw and blend 2 chemical concentrates into the water stream at the same time to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the foam hose and fan nozzle at distances up to 13 feet.



- Simultaneously blends 2 chemicals
- Projects rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Optional zero degree nozzle for increased foam throw
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a stainless steel foamer body for pressures over 700 PSI (#918115DU)
- See other high pressure foamers in Catalog 3

Includes

- · Stainless steel mounting bracket
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with polypropylene open flow foam wand and fan nozzle



Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square# 224200Jug Rack, SS, 2 1/2 Gallon# 224210Jug Rack, SS, 5 Gallon, Round/Square# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Optional Zero Degree Foam Nozzle (For Increased Range)

Nozzle, NPB, 1/2" - 00200 # 180144

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315 Check Valve, Air, SS/Viton, 1/4" # 491306

REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 400 to 700 PSI

 Flow
 2.0 GPM @ 700 PSI

Supply Line 1/2"

Hose 1/2" ID x 50' **Nozzle** 50250

Dilution Ratio Range 454:1 to 6:1 @ 700 PSI

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Industrial
- And Many Other Applications!



