

Portable 20 Gallon PD Precision Foamer

MODEL # 935170

OVERVIEW

The Portable 20 Gallon PD Precision Foamer is a low volume foam applicator that is ideal for jobs where precision application and tight control of overspray are required such as for cleaning restaurant hoods and vents. This unit features an all stainless steel cart assembly and on-board 110V air-compressor. An air-operated, double-diaphragm FloJet Pump draws ready-to-use chemical from a the 20 gallon tank and injects compressed air to create rich, clinging foam which greatly increases volume and coverage ability. The foam is then projected through the discharge hose, trigger gun and fan nozzle.

Key Features

- Projects a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Draws ready-to-use chemical solution
- 20 gallon tank reduces downtime for refilling trips
- Adjustable foam consistency (wet/dry)
- An on-board, quiet, 110V compressor drives the pump
- Chemical resistant wetted components ensure durability and years of reliable service
- Available as wall-mounted unit (#935155)
- See other air-operated foamers and sprayers in [Catalog 4](#)

Includes

- All stainless steel 4-wheel cart, locking enclosure and integrated stainless steel hose rack
- Non-marking tires & stainless steel swivel casters
- 20 gallon, wide-mouth, polyethylene chemical tank
- Air compressor (110 Volt)
- FloJet AODD pump with Santoprene diaphragm
- Air inlet ball valve
- Stainless steel precision foamer body
- 50' discharge hose and polypropylene trigger gun, wand with stainless steel nozzle

OPTIONS

Extended Hose (Order in 25' Increments)

Hose, Twin Line, Blue (Added to Standard Length) # 800100FT

Alternate Seal Materials - Santoprene Standard

Viton Upgrade: Flojet Air Pump & Check Valves # 710756

Kalrez Upgrade: Flojet Air Pump & Check Valves # 710755

Alternate Air Check Valve - EPDM Standard

Check Valve, Air, SS, 1/4" MM (Viton / Hast) # 491306

APPLICATIONS

- Hood & Vent Cleaning
- Restaurants
- Food & Beverage
- Hatchery
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Ready-to-Use Chemical Solution

Solution Temperature 120°F MAX

Electric 110V - Min.15 AMP Circuit

