

MODEL # 980106

## **OVERVIEW**

The 2-Way 105HC Mixing Station has a water flow rate of 1 GPM @ 40 PSI and is a "high concentrate" 2-chemical proportioner for filling smaller sized containers with strong solutions. This venturi injection system uses city water pressure (40 - 80 PSI) to draw and blend a high concentration of chemical into the water stream to create up to 1:1 dilution ratios. Use ball valves to switch between chemicals. Ball valve activation allows for hands-free dispensing.



- Achieves strong dilution ratios, up to 1:1 (with water thin chemicals)
- · Weaker ratios controlled by precision metering tips & plugs
- Designed to blend 2 different chemicals, or 2 different concentrations of the same chemical
- Water flow rate of 1 GPM @ 40 PSI for filling smaller containers and equipment
- Eliminates manual mixing and optimizes chemical utilization, employee safety and labor efficiency
- Ball valve activation allows for hands-free dispensing
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Draws chemical concentrate from any sized container
- Available for just one chemical (#980105)
- See other chemical management systems in Catalog 9

### Includes

- · Stainless steel mounting bracket
- Stainless steel inlet ball valve
- · Chemical ball valves
- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- Metering plugs to set 2:1 and 3:1 dilution ratios
- 10' open flow discharge hose

# **OPTIONS**

### Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

# Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square# 224200Jug Rack, SS, 2 1/2 Gallon# 224210Jug Rack, SS, 5 Gallon, Round/Square# 224215

# Alternate Check Valve - Viton Standard

Check Valve, Chemical, PP, 1/2" HB (EPDM) # 491403

# Lafferty Lafferty 2-WAY 105HC MIXING STATION Martina ACMICA \*\*\*COMMINION \*\*\*COMM

# REQUIREMENTS

# **Chemical Concentrate**

# Water

Temperature up to 160°F
Pressure 40 to 80 PSI
Flow 1.0 GPM @ 40 PSI

Supply Line 1/2"

Hose 1/2" ID x 10'

**Dilution Ratio Range** 229:1 to 1:1 @ 40 PSI



- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- And Many Other Applications!

