

# DBM A-25SS Asphalt Release Airless Foamer

MODEL # 974726

## OVERVIEW

The DBM A-25SS Asphalt Release Airless Foamer is a drum-mounted, medium volume foam applicator for projecting asphalt release chemicals on to truck beds or tools to prevent asphalt from sticking, without compressed air. This stainless steel venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate directly from the drum into the water stream to create an accurately diluted solution. The solution then flows through the discharge hose and wand to the "airless" foam wand which draws in atmospheric air to create and project wet, clinging foam.



## Key Features

- No compressed air required
- Stainless steel body for maximum durability
- Screws into, and dispenses directly from, chemical concentrate drums for increased efficiency
- Equipped with both fine and coarse threads
- Dilutes and projects asphalt release chemicals on to truck beds and asphalt tools as wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Available with a polypropylene body (#974114)
- See other industrial chemical applicators in [Catalog 8](#)

## Includes

- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 25' foam hose, stainless steel ball valve & extension wand
- Machined polypropylene airless foam wand

## OPTIONS

### Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

### Stainless Steel Airless Foam Wand

Wand, SS, Airless Foam, A-25SS # 536625SS

## REQUIREMENTS

### Chemical Concentrate

### Water

Temperature up to 180°F  
Pressure 35 to 125 PSI  
Flow 1.3 GPM @ 40 PSI  
Supply Line 1/2"

### Hose

1/2" ID x 25'

### Nozzle

A-25 Airless Foam Wand

### Dilution Ratio Range

297:1 to 4:1 @ 40 PSI

## APPLICATIONS

- Asphalt