Lafferty Equipment Manufacturing, LLC
Installation & Operation Instructions

Model # 536622 · Wand, PP, Airless Foam, PF416

REQUIREMENTS / SPECIFICATIONS

Requires RTU Chemical Solution	
Temperature	up to 160°F
Pressure	40-125 PSI
Solution Flow Rate	
#536106-6 *#6 Bullet Foam Nozzle, 1/2" FPT*	0.6 GPM @ 40 PSI
#536110-6 *#10 Bullet Foam Nozzle, 1/2" FPT*	1.0 GPM @ 40 PSI
#535539 *Wand, PP, Airless Foam, PF39*	1.5 GPM @ 40 PSI
#535531 *Wand, PP, Airless Foam, PF31*	2.0 GPM @ 40 PSI
#536619 *Wand, PP, Airless Foam, PF314*	3.8 GPM @ 40 PSI
#536621 *Wand, PP, Airless Foam, PF316*	6.3 GPM @ 40 PSI
#536622 *Wand, PP, Airless Foam, PF416*	8.0 GPM @ 60 PSI



Lafferty EQUIPMENT MANUFACTURING LLC

CFS TECHNOLOGIES

www.laffertyequipment.com
501-851-2820

WARNING! READ ALL INSTRUCTIONS BEFORE USING EQUIPMENT!

OVERVIEW

Pump Fed Airless Foam wands are designed for use with ready-to-use chemical solution supplied by a pump or central chemical feed system at 40-125 PSI. Chemical solution flows through the airless foam wand which draws in atmospheric air to create and project wet clinging foam.

PREVENTIVE MAINTENANCE: When the unit will be out of service for extended periods, place chemical tube(s) in water and flush the chemical out of the unit to help prevent chemical from drying out and causing build-up. Periodically check and clean chemical strainer and replace if missing.