





2-Way Ultimate Foamer

MODEL # 914107-G

OVERVIEW

The 2-Way Ultimate Foamer is a medium volume foam applicator for projecting up to 2 foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrates into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 12 feet. Use the chemical ball valves to inject the 2 chemicals separately or simultaneously. Gauges display incoming water and air pressure.

Key Features

- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Designed to apply 2 separate chemicals or 2 different concentrations of the same chemical
- Chemicals can be applied separately or simultaneously by adjusting the ball valves
- Designed for cleaning medium to large surfaces
- Fan pattern nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Industrial-strength wetted components ensure maximum chemical resistance and durability for years of outstanding performance with minimal maintenance
- See other configurations of Lafferty city water pressure foamers in Catalog 1

Includes

- Stainless steel mounting bracket
- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle





OPTIONS

Stainless Steel Hose Racks	
Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon, Round/Square	# 224215
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101
Alternate Check Valves - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306
Stainless Steel Foam Wand (Upgrade)	
Convert PP Wand to SS (New Units)	# 536603-X

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Pharm/Bio
- And Many Other Applications!

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	1.34 GPM @ 40 PSI
Supply Line	1/2"
Compressed Air	up to 3 CFM
Hose	3/4" ID x 50'
Nozzle	50250
Dilution Ratio Range	306:1 to 6:1 @ 40 PSI

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com