# 2-Way LC Foamer

**MODEL # 915107-G**











## OVERVIEW

The 2-Way LC Foamer is a medium volume foam applicator for projecting up to 2 foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrates into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 12 feet. Use the chemical ball valves to inject the 2 chemicals separately or simultaneously. Gauges display incoming water and air pressure.

### Key Features

- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Designed to apply 2 separate chemicals or 2 different concentrations of the same chemical
- Chemicals can be applied separately or simultaneously by adjusting the ball valves
- Designed for foam cleaning medium to large surfaces
- an pattern nozzle for quick coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available for only 1 chemical (#915105-G)
- See other configurations of Lafferty city water pressure foamers in Catalog 1




### Includes

- Stainless steel mounting bracket
- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- Chemical ball valves
- 20 color-coded metering tips to set dilution ratios
- 40' discharge hose, stainless steel ball valve, polypropylene foam wand and fan nozzle

## OPTIONS

| | |
|---|---|
| **Stainless Steel Hose Racks** | |
| Large Stainless Steel Hose Rack | # 224150 |
| **Stainless Steel Jug Racks** | |
| Jug Rack, SS, 1 Gallon, Round/Square | # 224200 |
| Jug Rack, SS, 2 1/2 Gallon | # 224210 |
| Jug Rack, SS, 5 Gallon, Round/Square | # 224215 |
| **Safe Flow Lid™ for 1 Gallon Jugs** | |
| Lid, Suction Tube, and Strainer | # 709101 |
| **Alternate Check Valves - EPDM Standard** | |
| Check Valve, Chemical, PP/Viton, 1/4" | # 491315 |
| Check Valve, Air, SS/Viton, 1/4" | # 491306 |

## REQUIREMENTS

| | |
|---|---|
| **Chemical Concentrate** | |
| **Water** | |
| Temperature | up to 160°F |
| Pressure | 35 to 125 PSI |
| Flow | 1.34 GPM @ 40 PSI |
| Supply Line | 1/2" |
| **Compressed Air** | up to 3 CFM |
| **Hose** | 3/4" ID x 40' |
| **Nozzle** | 50250 |
| **Dilution Ratio Range** | 306:1 to 6:1 @ 40 PSI |

## APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- Industrial
- Metal Processing

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com