Portable 5 Gallon A-20SS Airless Foamer

MODEL # 917910











OVERVIEW

The Portable A-20SS Airless Foamer is a 3.1 GPM @ 700 PSI foam applicator for projecting foaming chemicals on to any surface up close or at a distance without compressed air. Featuring an all stainless steel cart assembly, this stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. The solution then flows through the discharge hose and trigger gun to the "airless" foam wand which draws in atmospheric air to create and project wet, clinging foam at distances up to 12 feet.

Key Features

- No compressed air required
- Designed for foam cleaning medium to large sized areas
- Projects wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan nozzle for fast coverage at distances up to 10' and zero degree nozzle for up to 12' foam throw (depending on water pressure)
- Stainless steel components ensure years of outstanding performance with minimal maintenance
- Available as a wall-mounted unit (#917905)
- See other configurations of Lafferty high water pressure foamers in Catalog 3

Includes

- All stainless steel 2-wheel cart with non-marking tires & integrated hose rack
- Stainless steel, round, 5 gallon jug rack (square available)
- Machined stainless steel injector body
- Machined stainless steel airless foam wand
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose & trigger gun
- Fan nozzle & zero degree nozzle



OPTIONS

5 Gallon Pail

Pail, 5 Gallon Round W/ Suction Stem	# 709105

Square Jug Rack Conversion

Specify Round or Square Jug Racks at time of order

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer	# 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, SS, Viton, 1/4"	# 491324-V

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Pharm/Bio
- And Many Other Applications!

REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 180°F
Pressure	400 to 1000 PSI
Flow	3.1 GPM @ 700 PSI
Supply Line	3/8"
Hose	3/8" ID x 50'
Nozzle	A-20 Airless Foam Wand
Dilution Ratio Range	711:1 to 7:1 @ 700 PSI

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com