
Pump Fed XV Foamer

MODEL # 919305











OVERVIEW


The Pump Fed XV Foamer is a high volume foam applicator for projecting ready-to-use foaming chemicals on to any surface up close or at distances up to 15 feet (25 feet with zero degree nozzle). This unit receives ready-to-use chemical solution from a central chemical feed system and creates rich, clinging foam by injecting compressed air into the solution to greatly increase volume and coverage ability. A high volume of foam is then projected through the discharge hose and foam nozzle.

Key Features

- Receives ready-to-use chemical solution from a central chemical feed system
- Designed for foam cleaning large surfaces and areas
- Projects a high volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 15' range)
- Covers up to 500 sq ft (46.5 sq m) in 1 minute
- Zero degree nozzle for up to 25' range
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a lower flow rate (#920105)
- See other pump-fed applicators in Catalog 5
- Design the optimal central chemical feed system with the Lafferty Pump-Fed Central System Calculator

Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene foamer body
- 50' discharge hose
- Polypropylene foam wand with fan and zero degree nozzles



OPTIONS

Stainless Steel Hose Racks	
Large Stainless Steel Hose Rack	# 224150
Foam Solution Check Valves & Strainer	
Check Valve, PP, 1/2" (EPDM)	# 491409
Check Valve, PP, 1/2" (Viton)	# 491411
Check Valve, 316SS, 1/2", MF (Teflon)	# 491348SS-T
Strainer, "Y", SS, 1/2" MF	# 150350-1
Alternate Air Check Valve - EPDM Standard	
Check Valve, Air, SS, 1/4" MM (Viton / Hast)	# 491306
Stainless Steel Foam Wand, HV (Upgrade)	
Convert PP Wand to SS (New Units)	# 536605-X

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Military
- Paper Mill
- Pharm/Bio
- And Many Other Applications!

REQUIREMENTS

Ready-to-Use Chemical Solution	
Temperature	up to 160°F
Pressure	35 to 100 PSI
Flow	4 GPM @ 40 PSI
Supply Line	1/2"
Compressed Air	up to 6 CFM
Hose	1" ID x 50'
Nozzle	00400 & 50400

Lafferty
EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com