Pump Up Foamer Pro, 3 Gallon (EPDM Seals)

MODEL # 925005-E











OVERVIEW

The 3 Gallon Pump-Up Foamer Pro is a portable foam applicator for applying foaming chemicals to any surface as high-quality, rich, clinging foam. The EPDM o-rings and internal seals are resistant to caustic chemicals, which are commonly used for hood and vent cleaning. This professional model projects foam in a wide fan pattern for quick, but still precise, foam coverage. The 3 Gallon Pump-Up Foamer Pro features a heavy-duty hose, trigger gun, and extension wand and combines the many advantages of foam cleaning with the familiar ease and portability of a typical pump-up sprayer. If compressed air is available, use the "quick charge" valve to eliminate pumping!

Key Features

- Creates rich, clinging foam that adheres to surfaces longer to maximize chemical effectiveness
- Combines the advantages of foam application with the familiar ease and portability of a pump-up sprayer
- Projects the ideal amount of foam for small or large jobs requiring maximum portability
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Just fill the tank with ready-to-use chemical solution, pump it up and foam!
- Use the "quick charge" valve to pressurize with an air compressor instead of pumping (must disconnect airline during operation)
- Heavy-duty, easy-grip trigger gun with locking latch
- Wide fan pattern nozzle for fast application
- EPDM o-rings and internal seals are resistant to caustic chemicals, ideal for hood and vent cleaning
- Available with Viton/Nitrile seals (#925005)
- Available with a 1.5 gallon tank (#925004-E)
- Prepare perfectly blended chemical solutions with a Lafferty Mixing Station
- See other portable chemical applicators in Catalog 11

Includes

- Heavy-duty 3 gallon polyethylene tank with UV inhibitor
- Tank stabilizing base
- Heavy-duty manual pump
- EPDM seals and o-rings (Viton/Nitrile kit available)
- Tube of silicone grease
- Pressure relief valve
- Compressed air "quick charge" valve
- Machined foamer body
- 6' discharge hose
- Heavy-duty trigger gun with EPDM internal seals
- Polypropylene 10" wand & stainless steel fan nozzle



REQUIREMENTS

Ready-to-Use Chemical Solution

Temperature	up to 120°F
Accepts Compressed Air	up to 45 PSI

OPTIONS

Repair Kit

O Ring & Seal Repair Kit (Viton)	# 709040
O-Ring & Seal Repair Kit (EPDM)	# 709040-E
Silicone Lubricant, 5 Gram Tube	# 709049

Proportioning / Filling Options

1-Way Ball Valve Mixing Station (4 GPM)	# 985100
1-Way Push Lever Mixing Station (4 GPM)	# 981100

Optional Zero Degree Nozzle (For Increased Range)

Nozzle, SS, 1/4" - 0030	# 180030

APPLICATIONS

- Hood & Vent
- Restaurants
- Caustic/Alkaline Chemicals
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- Industrial

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com

- Janitorial/Sanitation