1-Way MT-AP Solvent Sprayer

MODEL # 930110











OVERVIEW

The 1-Way MT-AP Solvent Sprayer is a solvent spray applicator for either applying neat chemical or diluting "on-the-fly". This system is designed for facilities with low or no water pressure. It is suitable for handling many solvents (including d-limonene) and features a lockable, stainless steel enclosure. It uses a 3/8" Warren Rupp air-operated, double-diaphragm pump to draw either ready-to-use chemical from a static tank or a chemical concentrate and water from two tanks and blend them using precision metering tips. The solution is then projected through the discharge hose, trigger gun, wand and fan nozzle.

Key Features

- Solvent-resistant wetted components ensure durability with minimal maintenance
- Rugged Kynar/Teflon Warren Rupp AODD pump
- Projects neat chemical or dilutes concentrate "on-the-fly"
- Requires only compressed air to draw from static tanks
- Fan pattern spray for fast, efficient application
- Available for exclusively pre-diluted chemicals (#930109)
- See other industrial chemical applicators in Catalog 8

Includes

- Lockable, stainless steel pump enclosure
- Air inlet ball valve & air regulator/filter
- Machined polypropylene manifold
- 3/8" Warren Rupp AODD pump (Kynar/Teflon diaphragms)
- Solvent-resistant pickup tubes & 50' discharge hose
- Trigger gun, stainless steel extension wand & fan nozzle



OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack	# 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon, Round/Square	# 224215

Drum & Tote Stick Lengths & Seal Materials

Drum Stick, 33" (Viton or EPDM)	# 491643 / 491643-E
Drum Stick, 48" (Viton or EPDM)	# 491648 / 491648-E
Drum Stick, 54" (Viton or EPDM)	# 491645 / 491645-E
Tote Stick, 33" (Viton or EPDM)	# 491653 / 491653-E
Tote Stick, 48" (Viton or EPDM)	# 491654 / 491654-E
Tote Stick, 54" (Viton or EPDM)	# 491656 / 491656-E

Proportioning / Filling Options

1-Way Ball Valve SS Mixing Station (4 GPM)	# 985100SS

REQUIREMENTS

Ready-to-Use Chemical Solution	
Compressed Air	up to 4 CFM
Hose	1/2" ID x 50'
Nozzle	2515
Dilution Ratio Range	457:1 to 3:1 @ 60 PSI

APPLICATIONS

- Agriculture/Horticulture
- Asphalt
- Concrete
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Pharm/Bio
- Any Solvent Spraying!



Lafferty
EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com