Stationary 455 4-Way Fogger

MODEL # 950652











OVERVIEW

The Stationary 455 4-Way Fogger is a dry mist sprayer that uses compressed air (70 CFM @ 80 PSI) and venturi action to draw ready-to-use chemical solution from a nearby container and project it up to 35 feet in 4 directions. The adjustable output sprays mist (fog) into the air to cover exposed surfaces and penetrate hard-to-reach areas. This versatile unit can be used as a 2-Way fogger by closing ball valves on two fogger bodies. It can be permanently mounted or easily moved.

Key Features

- Can be permanently mounted or moved for use in multiple locations
- Atomizes and sprays chemical solutions using only compressed air
- Venturi action draws pre-diluted chemical from a nearby container
- Projects up to 35' in 4 directions
- Ball valves on two fogger bodies allow for conversion to 2-Way fogging for narrow areas
- Dry fog (mist) fills the air and covers exposed surfaces with chemical, including hard-to-reach areas
- 455 foggers produce drier output, without adjustments, compared to other fogger series (633, 305, etc.)
- *Optional* metering tips can further reduce chemical usage and output wetness
- Chemical resistant polypropylene construction ensures durability and years of outstanding performance
- See Catalog 7 for hand held, permanently mounted and portable foggers
- Use the Lafferty Fogger Planning Tool to design the optimal fogging system for any facility

Includes

- Polypropylene base/mounting plate
- Table standoffs
- 1/2" NPT air inlet
- (4) Machined polypropylene fogger bodies
- (2) Air ball valves
- (4) Metering tip holders
- (2) 10' chemical suction tubes and strainers



REQUIREMENTS

Ready-to-Use Chemical Solution	
Compressed Air	up to 70 CFM @ 80 PSI
Minimum Air Supply Line	1/2"



OPTIONS

Optional Check Valves to Keep Tubes Primed	
Check Valve, Chemical, PP(W), 1/4" (EPDM)	# 491401
For Lighter Fog Use Metering Tips (4 Sets)	
Metering Tips-Color Coded (10 Smallest)	# 443794
Proportioning / Filling Options	
1-Way Ball Valve Mixing Station (4 GPM)	# 985100
1-Way Push Lever Mixing Station (4 GPM)	# 981100
Quick-Disconnect Set for Air Inlet	
QD, SS, Plug, 1/2" MPT	# 350459
QD, SS, Socket, 1/2" FPT	# 350455

APPLICATIONS

- Sanitizers
- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Industrial
- Odor Control
- Pharm/Bio
- And Many Other Applications!

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com