Portable 20 Gallon 455 4-Way SS Fogger

MODEL # 950722-SS











OVERVIEW

The Portable 20 Gallon 455 4-Way Stainless Steel Fogger is a dry mist sprayer that uses compressed air (70 CFM @ 80 PSI) and venturi action to draw ready-to-use chemical solution from the tank on the stainless steel cart and project it up to 35 feet in 4 directions. The adjustable output sprays mist (fog) into the air to cover exposed surfaces and penetrate hard-to-reach areas. This unit features stainless steel fogger bodies, a telescoping mast, and can also be used as a 2-Way fogger.

Key Features

- Atomizes and sprays chemical solutions using only compressed air
- Venturi action draws pre-diluted chemical from the onboard tank
- Projects up to 35' in 4 directions
- Ball valves on two fogger bodies allow for conversion to 2-Way fogging for narrow areas
- Dry fog (mist) fills the air and covers exposed surfaces with chemical, including hard-to-reach areas
- 455 foggers produce drier output, without adjustments, compared to other fogger series (633, 305, etc.)
- *Optional* metering tips can further reduce chemical usage and output wetness
- Variable height adjustment up to 80"
- Stainless steel fogger bodies and overall construction ensures durability and years of outstanding performance
- See Catalog 7 for hand held, permanently mounted and portable foggers
- Use the Lafferty Fogger Planning Tool to design the optimal fogging system for any facility

Includes

- All stainless steel 4-wheel cart with non-marking tires and stainless steel swivel casters
- 20 gallon, wide-mouth, polyethylene chemical tank
- Stainless steel, adjustable height fogger pole
- (4) Machined stainless steel fogger bodies
- (2) Air ball valves
- (4) Stainless steel metering tip holders
- (2) 10' chemical suction tubes and strainers



OPTIONS

Optional Check Valves to Keep Tubes Primed	
Check Valve, Chemical, SS, EPDM, 1/4"	# 491324
For Lighter Fog Use Metering Tips (4 Sets)	
Metering Tips-Color Coded (10 Smallest)	# 443794
Proportioning / Filling Options	
1-Way Ball Valve Mixing Station (4 GPM)	# 985100
1-Way Push Lever Mixing Station (4 GPM)	# 981100
High Volume Mixing Station (9.9 GPM)	# 985835

APPLICATIONS

- Odor Control
- Fumigation
- Insecticides
- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

REQUIREMENTS

Ready-to-Use Chemical Solution	
Compressed Air	up to 70 CFM @ 80 PSI
Minimum Air Supply Line	1/2"

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com