W-25 Spray-All

MODEL # 970225











OVERVIEW

The W-25 Spray-All is a water-driven, medium volume spray applicator for applying chemical solutions to a variety of surfaces. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a uniform spray. With a flow rate of just over 1 gallon per minute, this unit is great for spraying virtually any sized area or object quickly and completely.

Key Features

- Creates a medium volume spray (1.34 GPM @ 40 PSI)
- Designed for spraying any sized object with minimal over-spray
- Fan pattern nozzle for fast coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Use it where 35-125 PSI water is available
- Available with lower or higher flow rates (#970220, 970270)
- See other Lafferty Spray-Alls and more chemical applicators in Catalog 1

Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle



OPTIONS

Stainless Steel Hose Racks	
Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101
Alternate Check Valve - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315

APPLICATIONS

- Heavy Degreasing
- Agriculture/Horticulture
- Food & Beverage
- Hood & Vent
- Industrial
- Metal Processing
- Paper Mill
- And Many Other Applications!

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	1.34 GPM @ 40 PSI
Supply Line	1/2"
Hose	1/2" ID x 50'
Nozzle	2540
Dilution Ratio Range	306:1 to 6:1 @ 40 PSI

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com