Electric W-25 Asphalt Release Sprayer


MODEL # 974212











OVERVIEW

The Electric W-25 Asphalt Release Sprayer is a spray applicator for diluting and spraying asphalt release chemicals on to truck beds or tools to prevent asphalt from sticking. Designed for facilities with low or no water pressure. An electric pump draws water from a static tank and provides the water pressure to power a venturi injector. The injector draws chemical concentrate from any container and blends it into the water stream to create an accurately diluted solution using precision metering tips. The solution is then projected through the discharge hose, wand and fan nozzle.

Key Features

- Projects asphalt release chemicals on to truck beds and asphalt tools as a spray
- The 120V electric pump draws water from a static tank to drive the venturi injector
- Venturi injector dilutes chemical concentrates "on-the-fly"
- No chemical passes through the pump
- Fan pattern spray for fast, efficient application
- Chemical resistant wetted components
- Available with a run/delay timer (#974212-TD)
- See other industrial chemical applicators in Catalog 8

Includes

- Lockable, stainless steel pump enclosure
- 120V Electric pump
- Machined polypropylene injector body
- 25' discharge hose with stainless steel ball valve
- Stainless steel wand & fan nozzle



OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack	# 224145

Drum & Tote Stick Lengths & Seal Materials

Drum Stick, 33" (Viton or EPDM)	# 491643 / 491643-E
Drum Stick, 48" (Viton or EPDM)	# 491648 / 491648-E
Drum Stick, 54" (Viton or EPDM)	# 491645 / 491645-E
Tote Stick, 33" (Viton or EPDM)	# 491653 / 491653-E
Tote Stick, 48" (Viton or EPDM)	# 491654 / 491654-E
Tote Stick, 54" (Viton or EPDM)	# 491656 / 491656-E

Alternate Chemical Check Valve - Viton Standard

Check Valve, Chemical, PP(W), 1/4" (EPDM)	# 491401

APPLICATIONS

- Asphalt



***536500** Insulator for 1/4" SS Wand*

Insulates hands from hot or cold extremes and provides comfortable secure grip.

REQUIREMENTS

Chemical Concentrate
Static Tank of Water

Hose	1/2" ID x 25'
Nozzle	2540
Electric	120V
Dilution Ratio Range	343:1 to 3:1 @ 50 PSI

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com