DBM W-25SS Asphalt Release Spray-All

MODEL # 974626







OVERVIEW

The DBM W-25SS Asphalt Release Spray-All is a water-driven, drum-mounted, stainless steel spray applicator for applying asphalt release agents on to truck beds or tools to prevent asphalt from sticking. This venturi injection system uses city water pressure (35 - 125 PSI) to draw and blend chemical concentrate directly from the drum into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a uniform spray. With a flow rate of around 1.3 GPM @ 40 PSI, this unit is great for spraying down any vehicle or equipment quickly and efficiently.



Key Features

- Designed for diluting and spraying asphalt release agents on to truck beds and asphalt tools
- Mounts to, and dispenses directly from, chemical drums for increased efficiency
- Stainless steel construction for maximum durability and chemical resistance
- Creates a 1.3 GPM @ 40 PSI, fan pattern spray for fast and even coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Available with a polypropylene body (#974600)
- See other Lafferty asphalt release equipment and industrial chemical applicators in Catalog 8

Includes

- Machined stainless steel injector body
- 20 color-coded precision metering tips to set dilution ratios
- 25' discharge hose
- All stainless steel ball valve, wand & fan nozzle

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 180°F
Pressure	35 to 125 PSI
Flow	1.3 GPM @ 40 PSI
Supply Line	1/2"
Hose	1/2" ID x 25'
Nozzle	2540
Dilution Ratio Range	297:1 to 3:1 @ 40 PSI

APPLICATIONS

- Asphalt
- Form Release

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack	# 224145

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com