Soft Brush Airless Foamer

MODEL # 975515







OVERVIEW

The Soft Brush Airless Foamer is a foam cleaning system that continually creates foam through the soft bristle brush, without compressed air. This venturi injection system uses city water pressure (40 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution using precision metering tips. The solution then flows through the hose and handle to the "airless" foamer which draws in atmospheric air to create an optimal volume of wet, clinging foam in the brush. The soft bristled brush will not damage paintwork or scratch surfaces and the foam continually flushes debris from the bristles.

Key Features

- No compressed air required
- The industrial quality, soft bristle brush will not damage paintwork or other delicate surfaces
- Creates a low volume of wet, clinging foam which increases chemical contact time and effectiveness
- Foam continually flushes debris from the bristles
- Turn the foam on and off at the handle
- Highly effective, even with minimal water pressure
- Chemical resistant wetted components ensure durability and years of reliable performance
- See other city water pressure applicators in Catalog 1

Includes

- Inlet and discharge ball valves
- Machined polypropylene injector body
- 10 color-coded metering tips for setting dilution ratios
- 50' discharge hose and 44" rubber coated handle
- Stainless steel foamer body and soft bristle brush



OPTIONS

Stainless Steel Hose Racks	
Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon, Round/Square	# 224215
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101
Alternate Check Valve - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315

APPLICATIONS

- Vehicle Wash
- Agriculture/Horticulture
- Animal Health
- Industrial
- Supermarkets
- And Many Other Applications!

REQUIREMENTS

Chemical Concentrate

Water	
Temperature	up to 160°F
Pressure	50 to 125 PSI
Flow	0.45 GPM @ 50 PSI
Supply Line	1/2"
Hose	3/8" ID x 50'
Nozzle	Foam Brush Head, Soft Bristle
Dilution Ratio Range	103:1 to 4:1 @ 50 PSI

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com