Soft Brush Foamer

MODEL # 975525







OVERVIEW

The Soft Brush Foamer is a foam cleaning system that continually creates foam through the soft bristle brush. This venturi injection system uses city water pressure (50 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution using precision metering tips. Rich, clinging foam is created by injecting compressed air into the solution to greatly expand volume and coverage ability. An optimal volume of high-quality foam is then projected through the hose and handle into the brush. The soft bristled brush will not damage paintwork or scratch surfaces and the foam continually flushes debris from the bristles.



Key Features

- The industrial quality, soft bristle brush will not damage paintwork or other delicate surfaces
- Creates a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foam continually flushes debris from the bristles
- Turn the foam on and off at the handle
- Chemical resistant wetted components ensure durability and years of reliable performance
- Available with a rough brush for tougher cleaning tasks (#975530)
- See other city water pressure applicators in Catalog 1

Includes

- Water and air inlet ball valves
- Machined polypropylene injector body
- 10 color-coded metering tips for setting dilution ratios
- 50' discharge hose and ball valve
- 44" rubber coated handle and soft bristle brush

OPTIONS

Stainless Steel Hose Racks	
Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon, Round/Square	# 224215
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101
Alternate Check Valves - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 160°F
Pressure	50 to 125 PSI
Flow	0.35 GPM @ 50 PSI
Supply Line	1/2"
Compressed Air	up to 0.5 CFM
Hose	1/2" ID x 50'
Nozzle	Foam Brush Head, Soft Bristle
Dilution Ratio Range	80:1 to 5:1 @ 50 PSI

APPLICATIONS

- Vehicle Wash
- Agriculture/Horticulture
- Animal Health
- Industrial
- Janitorial/Sanitation
- Supermarkets
- And Many Other Applications!

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com