









Electric FT 2-Way W-25HC Asphalt Release Sprayer

MODEL # 974220

OVERVIEW

The Electric FT W-25 2-Way Asphalt Release Sprayer is a spray applicator for diluting and projecting 2 asphalt release chemicals on to truck beds or tools to prevent asphalt from sticking. It is designed to work in facilities that have low or fluctuating water pressure. This system features a lockable, stainless steel enclosure and uses an electric pump to draw water from an integrated float tank and drive the system. A venturi injector draws chemical concentrates from any containers and blends them into the water stream to create accurately diluted solutions using precision metering tips. The solution is then projected through the discharge hose, wand and fan nozzle.

Key Features

- Projects 2 asphalt release chemicals on to truck beds and asphalt tools as a spray
- The 120V electric pump draws water from an internal float tank to drive the venturi injector
- Venturi injector dilutes chemical concentrates "on-the-fly"
- Alternate chemicals or concentrations using ball valves
- · No chemical passes through the pump
- Fan pattern spray for fast, efficient application
- Chemical resistant wetted components
- See other industrial chemical applicators in Catalog 8

Includes

- Lockable, stainless steel pump enclosure
- 120V Electric pump
- Internal water float tank
- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 25' discharge hose with stainless steel ball valve
- Stainless steel discharge ball valve, wand & fan nozzle

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

Heater Assembly

Retro-Fit Heater Assembly # 720981

Drum & Tote Stick Lengths & Seal Materials

 Drum Stick, 33" (Viton or EPDM)
 # 491643 / 491643-E

 Drum Stick, 48" (Viton or EPDM)
 # 491648 / 491648-E

 Drum Stick, 54" (Viton or EPDM)
 # 491645 / 491645-E

 Tote Stick, 33" (Viton or EPDM)
 # 491654 / 491654-E

 Tote Stick, 48" (Viton or EPDM)
 # 491654 / 491656-E

 Tote Stick, 54" (Viton or EPDM)
 # 491656 / 491656-E

Alternate Chemical Check Valve - Viton Standard

Check Valve, Chemical, PP(W), 1/4" (EPDM) # 491401

APPLICATIONS

Asphalt



REQUIREMENTS

Chemical Concentrate

 Temperature
 up to 160°F

 Pressure
 20 to 60 PSI

 Hose
 1/2" ID x 25'

 Nozzle
 2540

 Electric
 120V

Dilution Ratio Range 297:1 to 3:1 @ 40 PSI

