

A-40SS Airless Foamer

MODEL # 912905

OVERVIEW

The A-40SS Airless Foamer is a medium volume foam applicator for projecting foaming chemicals on to any surface up close or at distances up to 10 feet without compressed air. This venturi injection system uses boosted water pressure (125 - 350 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. The solution then flows through the discharge hose and trigger gun to the "airless" foam wand which draws in atmospheric air to create and project wet, clinging foam.

Key Features

- No compressed air required
- Designed for foam cleaning medium to large sized areas
- Projects wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Projects foam up to 10' (depending on water pressure)
- Chemical resistant components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available as a portable system with a stainless steel cart assembly (#912910)
- See other configurations of Lafferty boosted water pressure foamers in [Catalog 2](#)

Includes

- Stainless steel mounting bracket
- Stainless steel inlet ball valve
- Machined stainless steel injector body
- Machined stainless steel airless foam wand
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose & trigger gun

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, SS, Viton, 1/4" # 491324-V

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Vehicle Wash
- Dairy
- Industrial
- Paper Mill
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 180°F
Pressure 125 to 350 PSI
Flow 2.84 GPM @ 250 PSI
Supply Line 1/2"

Hose

3/8" ID x 50'

Nozzle

A-40SS Airless Foam Wand

Dilution Ratio Range

649:1 to 13:1 @ 250 PSI