Hyper SSDU Foamer

MODEL # 917115DU

OVERVIEW

The Hyper SSDU Foamer is a 3.3 GPM @ 700 PSI foam applicator for simultaneously projecting 2 foaming chemicals on to any surface up close or at a distance. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend 2 chemical concentrates into the water stream at the same time to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the foam hose, wand and fan nozzle at distances up to 13 feet.

Key Features

- · Simultaneously blends 2 chemicals into the water stream
- Stainless steel foamer body for maximum durability and chemical resistance
- Projects a substantial volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 1.5 minutes
- Optional zero degree nozzle for increased foam throw
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- \bullet Available for a single chemical (#917115)
- See other high water pressure applicators in Catalog 3

Includes

- Stainless steel mounting bracket
- Machined stainless steel foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with open flow polypropylene foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks Large Stainless Steel Hose Rack	# 224150	
Stainless Steel Jug Racks		
Jug Rack, SS, 1 Gallon, Round/Square	# 224200	
Jug Rack, SS, 2 1/2 Gallon	# 224210	
Jug Rack, SS, 5 Gallon, Round/Square	# 224215	
Safe Flow Lid™ for 1 Gallon Jugs		
Lid, Suction Tube, and Strainer	# 709101	
Optional Zero Degree Nozzle (For Increased Range)		
Nozzle, NPB, 3/4" - 00400	# 180154	
Alternate Check Valves - EPDM Standard		
Check Valve, Chemical, PP/Viton, 1/4"	# 491315	
Check Valve, Air, SS/Viton, 1/4"	# 491306	

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Industrial
- Metal Processing
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 180°F
Pressure	400 to 1000 PSI
Flow	3.3 GPM @ 700 PSI
Supply Line	3/8"
Compressed Air	up to 5 CFM
Hose	3/4" ID x 50'
Nozzle	65300
Dilution Ratio Range	756:1 to 8:1 @ 700 PSI











