



MODEL # 976400

OVERVIEW

The Timed Entryway Ultimate Foam Sanitizer is an automated foam applicator for projecting sanitizing chemicals on to floors of 3' wide employee walk doors to prevent cross contamination. When activated, this venturi injection system uses city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. Foam is then projected through the discharge hose and Spreader™ nozzle. The system timer is user-programmable to meet the needs of any facility.



- Applies a layer of rich, clinging foam to entryway floors to prevent cross-contamination
- Designed for 3' wide employee walk doors
- Dilutes chemical concentrate "on-the-fly" from a container near the unit
- The unique Spreader™ nozzle lays a foam pattern 3' across and 4' wide to ensure all foot traffic and cart wheels are fully exposed to the sanitizer
- Automatic activation and shutoff for use in moderate to high traffic areas
- Adjustable timer controls the application of foam at regular intervals - up to 1 minute foaming and up to 1 hour off
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure durability and years of reliable service with minimal maintenance
- See Catalog 6 for other entryway configurations including pushbutton-activated, electric-eye-activated, dual doorway and more!



- Stainless steel mounting plate
- NEMA rated control box with run/delay timer
- Water activation solenoid
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- Foam enhancer
- 10' discharge hose
- Entryway Spreader™ nozzle

OPTIONS

Stainless Steel Jug Racks

224200
224200-L
224210
224214
224215

Dual Pick-up Assembly


Entryway Dual Chemical Pick-up Assembly # 976012

Alternate Chemical Check Valve - Viton Standard

Check Valve, Chemical, PP(W), 1/4" (EPDM) # 491401

Control Box Upgrades (Specify at Time of Purchase)

Photocell Activation Upgrade # 976001EE
Push Button Activation Upgrade # 976001PB



REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 35 to 125 PSI

 Flow
 1.34 GPM @ 40 PSI

Supply Line 1/2"

Compressed Air up to 3 CFM

Hose 3/4" ID x 10'

Nozzle Spreader Nozzle

Electric 120V

Dilution Ratio Range 306:1 to 6:1 @ 40 PSI

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Food & Beverage
- Hatchery
- Pharm/Bio
- Supermarkets
- And Many Other Applications!











