W-10SS Spray-All

MODEL # 918050

OVERVIEW

The W-10SS Spray-All is a water-driven spray applicator for applying chemical solutions to a variety of surfaces at 1.85 GPM @ 700 PSI. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrate into the water stream using precision metering tips. The accurately diluted solution is then projected through the discharge hose, trigger gun, wand and fan nozzle.

Key Features

- Designed for spraying down medium to large sized surfaces and objects
- Projects a chemical spray in a fan pattern for quick application (1.85 GPM @ 700 PSI)
- All stainless steel components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a higher flow rate (#918054)
- See other Lafferty high water pressure chemical applicators in Catalog 3

Includes

- Stainless steel mounting bracket
- Machined stainless steel injector body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, trigger gun, wand & fan nozzle

OPTIONS

Stainless Steel Hose Racks Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon, Round/Square	# 224215
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101

Alternate Check Valve - EPDM Standard Check Valve, Chemical, SS, Viton, 1/4"

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Metal Processing
- Military
- Paper Mill
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

491324-V

Chemical Concentrate

Water	
Temperature	up to 180°F
Pressure	400 to 1000 PSI
Flow	2.2 GPM @ 1000 PSI
Supply Line	3/8"
Hose	3/8" ID x 50'
Nozzle	2510
Dilution Ratio Range	423:1 to 6:1 @ 700 PSI









