

MODEL # 918105

OVERVIEW

The HP Foamer is a 2 GPM @ 700 PSI foam applicator for projecting foaming chemicals on to any surface up close or at a distance. This venturi injection system uses high water pressure (400 - 700 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the foam hose and fan nozzle at distances up to 13 feet.



- Projects rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Optional zero degree nozzle for increased foam throw
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a stainless steel foamer body for pressures over 700 PSI (#918115)
- Available with a higher flow rate (#917105- Hyper Foamer)
- See other Lafferty high water pressure chemical applicators in Catalog 3

Includes

- · Stainless steel mounting bracket
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with polypropylene open flow foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square# 224200Jug Rack, SS, 2 1/2 Gallon# 224210Jug Rack, SS, 5 Gallon, Round/Square# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Optional Zero Degree Foam Nozzle (For Increased Range)

Nozzle, NPB, 1/2" - 00200 # 180144

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315 Check Valve, Air, SS/Viton, 1/4" # 491306

□

FOAMER

REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 400 to 700 PSI

 Flow
 2.0 GPM @ 700 PSI

Supply Line 1/2"

 Compressed Air
 up to 5 CFM

 Hose
 1/2" ID x 50'

 Nozzle
 50250

Dilution Ratio Range 454:1 to 6:1 @ 700 PSI

APPLICATIONS

- Food & Beverage
- Animal Health
- Vehicle Wash
- Industrial
- Pharm/Bio
- And Many Other Applications!

