

Triple Foam Stick Set

MODEL # 910310

OVERVIEW

The Triple Foam Stick Set is a foam applicator designed for car-wash pre-soak, brush lubrication or to apply any 3 foaming products. This unit receives 3 ready-to-use chemicals from a pumping system and injects compressed air to increase the solution volume and create thick, rich, clinging foam. The foam is then evenly projected through the 7 foot foam stick assemblies. A fixed flow rate allows the user to use just one air valve to adjust the foam quality for all 3 foam sticks simultaneously. This system is great for retrofitting and for new installations.

Key Features

- Evenly applies 3 chemicals as rich, clinging foam
- Receives chemicals from a chemical pumping system
- Fixed flow rate to ensure consistent cost-per-application
- Easy to calibrate! Adjust all 3 foam sticks with a single air valve to achieve the desired foam consistency
- No moving or wear parts virtually eliminates the need for constant maintenance and parts replacement
- Chemical-resistant components ensure durability and years of reliable performance
- To allow for customization in any facility, this unit requires user-supplied tubing for installation (see requirements for tubing sizes)
- Available with a complete pumping system (#910330)
- Available as a single foam stick set (#910061)
- See more Lafferty vehicle wash equipment in [Catalog 10](#)

Includes

- 6 precision-drilled, clear PVC foam sticks (3 per assembly)
- 6 tube-lock solution check valves (Viton seals)
- 6 machined polypropylene foamer bodies
- 2 air adjustment needle valves (1 per assembly)


OPTIONS

Air and Chemical Tubing (Order in 10' Increments)

Air, Polyflow, 1/4" x 1'	# 475200FT
Solution, Pump to Tee, Polyflow, 1/2" x 1'	# 475400FT
Solution, Tee to Foamer, Polyflow, 3/8" x 1'	# 475300FT

Alternate Check Valve (Viton Standard)

TL Check Valve, PVC / EPDM, 3/8"	# 491456-E
----------------------------------	------------



REQUIREMENTS

Ready to Use Chemical Solution

Solution Pressure	40 - 60 PSI
Flow Rate	up to 1.55 GPM
Compressed Air	up to 1.5 CFM
Liquid tubing - pump to tee	1/2" I.D.
Liquid tubing - tee to foam sticks	3/8" I.D.
Tubing from air supply	1/4" I.D.

APPLICATIONS

- Tri-Color Foam
- Complete Wax Application
- Brush Lubrication
- Carwash Pre-Soak
- Vehicle Wash