

# 455 8-Way Fogger

MODEL # 950208

## OVERVIEW

The 455 8-Way Fogger is a dry mist sprayer that uses compressed air (140 CFM @ 80 PSI) and venturi action to draw ready-to-use chemical solution from a nearby container and project it up to 35 feet in 8 directions. The adjustable output sprays mist (fog) into the air to cover exposed surfaces and penetrate hard-to-reach areas.

## Key Features

- Atomizes and sprays chemical solutions using only compressed air
- Venturi action draws pre-diluted chemical from a nearby container
- Projects up to 35' in 8 directions
- Dry fog (mist) fills the air and covers exposed surfaces with chemical, including hard-to-reach areas
- 455 foggers produce drier output, without adjustments, compared to other fogger series (633, 305, etc.)
- *Optional* needle valve can further reduce chemical usage and output wetness
- Chemical pickup can be installed on the top or bottom
- Chemical resistant polypropylene construction ensures durability and years of outstanding performance
- See [Catalog 7](#) for hand held, permanently mounted and portable foggers
- Use the Lafferty [Fogger Planning Tool](#) to design the optimal fogging system for any facility

## Includes

- Machined polypropylene fogger body
- Metering tip holder
- 10' chemical suction tube and strainer

## OPTIONS

### Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215

### To Control Solution Flow (Wetness of Fog)

Needle Valve, PVC, 1/4" FM	# 660781
----------------------------	----------

## APPLICATIONS

- Odor Control
- Fumigation
- Insecticides
- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



## REQUIREMENTS

### Ready-to-Use Chemical Solution

**Compressed Air** up to 140 CFM @ 80 PSI

**Minimum Air Supply Line** 1/2"

