

# Soft Brush Airless Foamer

MODEL # 975515

## OVERVIEW

The Soft Brush Airless Foamer is a foam cleaning system that continually creates foam through the soft bristle brush, without compressed air. This venturi injection system uses city water pressure (40 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution using precision metering tips. The solution then flows through the hose and handle to the "airless" foamer which draws in atmospheric air to create an optimal volume of wet, clinging foam in the brush. The soft bristled brush will not damage paintwork or scratch surfaces and the foam continually flushes debris from the bristles.

## Key Features

- No compressed air required
- The industrial quality, soft bristle brush will not damage paintwork or other delicate surfaces
- Creates a low volume of wet, clinging foam which increases chemical contact time and effectiveness
- Foam continually flushes debris from the bristles
- Turn the foam on and off at the handle
- Highly effective, even with minimal water pressure
- Chemical resistant wetted components ensure durability and years of reliable performance
- See other city water pressure applicators in [Catalog 1](#)

## Includes

- Inlet and discharge ball valves
- Machined polypropylene injector body
- 10 color-coded metering tips for setting dilution ratios
- 50' discharge hose and 44" rubber coated handle
- Stainless steel foamer body and soft bristle brush

## OPTIONS

### Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

### Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

### Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

### Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

## APPLICATIONS

- Vehicle Wash
- Agriculture/Horticulture
- Animal Health
- Industrial
- Supermarkets
- And Many Other Applications!



## REQUIREMENTS

### Chemical Concentrate

#### Water

Temperature up to 160°F  
Pressure 50 to 125 PSI  
Flow 0.45 GPM @ 50 PSI  
Supply Line 1/2"

#### Hose

3/8" ID x 50'

#### Nozzle

Foam Brush Head, Soft Bristle

#### Dilution Ratio Range

103:1 to 4:1 @ 50 PSI