

MODEL # 975525

OVERVIEW

The Soft Brush Foamer is a foam cleaning system that continually creates foam through the soft bristle brush. This venturi injection system uses city water pressure (50 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution using precision metering tips. Rich, clinging foam is created by injecting compressed air into the solution to greatly expand volume and coverage ability. An optimal volume of high-quality foam is then projected through the hose and handle into the brush. The soft bristled brush will not damage paintwork or scratch surfaces and the foam continually flushes debris from the bristles.



- The industrial quality, soft bristle brush will not damage paintwork or other delicate surfaces
- Creates a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foam continually flushes debris from the bristles
- Turn the foam on and off at the handle
- Chemical resistant wetted components ensure durability and years of reliable performance
- Available with a rough brush for tougher cleaning tasks (#975530)
- See other city water pressure applicators in Catalog 1



- · Water and air inlet ball valves
- Machined polypropylene injector body
- 10 color-coded metering tips for setting dilution ratios
- 50' discharge hose and ball valve
- 44" rubber coated handle and soft bristle brush

Lafferty When the state of the

OPTIONS

| Stainless Steel Hose Racks Large Stainless Steel Hose Rack | # 224150 | | |
|---|----------|--|--|
| Stainless Steel Jug Racks | | | |
| Jug Rack, SS, 1 Gallon, Round/Square | # 224200 | | |
| Jug Rack, SS, 2 1/2 Gallon | # 224210 | | |
| Jug Rack, SS, 5 Gallon, Round/Square | # 224215 | | |
| Safe Flow Lid™ for 1 Gallon Jugs | | | |
| Lid, Suction Tube, and Strainer | # 709101 | | |
| Alternate Check Valves - EPDM Standard | | | |
| Check Valve, Chemical, PP/Viton, 1/4" | # 491315 | | |
| Check Valve, Air, SS/Viton, 1/4" | # 491306 | | |
| | | | |

REQUIREMENTS

Chemical Concentrate

Dilution Ratio Range

| Chemical Concentrate | |
|----------------------|----------------------------------|
| Water | |
| Temperature | up to 160°F |
| Pressure | 50 to 125 PSI |
| Flow | 0.35 GPM @ 50 PSI |
| Supply Line | 1/2" |
| Compressed Air | up to 0.5 CFM |
| Hose | 1/2" ID x 50' |
| Nozzle | Foam Brush Head, Soft Bristle |

80:1 to 5:1 @ 50 PSI

APPLICATIONS

- Vehicle Wash
- Agriculture/Horticulture
- Animal Health
- Industrial
- Janitorial/Sanitation
- Supermarkets
- And Many Other Applications!











