

Portable 60 Gallon Uni-Body Foamer

MODEL # 975860

OVERVIEW

The Portable 60 Gallon Uni-Body Foamer is a medium volume foam applicator featuring a 4-wheel, all stainless steel cart assembly with a 60 gallon chemical concentrate tank. It will project foaming chemicals on to any surface up close or at distances up to 12 feet. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate from the tank into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle.

Key Features

- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- 60 gallon chemical concentrate tank reduces downtime for refilling trips to the chemical room
- Fan pattern nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with 20 or 40 gallon chemical tank (#975820, 975840)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- All stainless steel 4-wheel cart with non-marking tires and integrated hose rack
- Heavy-duty, stainless steel swivel casters
- 60 gallon heavy-duty, wide-mouth chemical concentrate tank
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

OPTIONS

Alternate Check Valves - EPDM Standard

| | |
|---------------------------------------|----------|
| Check Valve, Chemical, PP/Viton, 1/4" | # 491315 |
| Check Valve, Air, SS/Viton, 1/4" | # 491306 |

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Military
- Paper Mill
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

| | |
|-------------|-------------------|
| Temperature | up to 160°F |
| Pressure | 35 to 125 PSI |
| Flow | 1.34 GPM @ 40 PSI |
| Supply Line | 1/2" |

Compressed Air

up to 3 CFM

Hose

3/4" ID x 40'

Nozzle

50250

Dilution Ratio Range

306:1 to 6:1 @ 40 PSI