Uni-Body MV Foamer

MODEL # 975560-G

OVERVIEW

The Uni-Body MV Foamer is a medium volume foam applicator (2.4 GPM @ 40 PSI) for projecting foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 14 feet. Gauges display incoming water and air pressure.



- The unique machined polypropylene uni-body design is both compact and cost-effective
- Designed for foam cleaning medium to large surfaces
- Creates a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for fast coverage (up to 14' range)
- Covers up to 500 sq ft (46.5 sq m) in 1.5 minutes
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Available with lower volume output (#975555-G)
- See other configurations of Lafferty city water pressure foamers in Catalog 1

Includes

- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid. Suction Tube, and Strainer # 709101

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315 Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Metal Processing
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 35 to 125 PSI

 Flow
 2.45 GPM @ 40 PSI

Supply Line 1/2"

 Compressed Air
 up to 4 CFM

 Hose
 3/4" ID x 40'

 Nozzle
 65300

Dilution Ratio Range 560:1 to 6:1 @ 40 PSI











