

TGSS Foamer

MODEL # 918101

OVERVIEW

The TGSS Foamer is a trigger gun foam applicator for projecting foaming chemicals on to any surface up close or at a distance. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose, trigger gun, and fan nozzle at distances up to 10 feet.

Key Features

- Stainless steel foamer body for durability and maximum chemical resistance
- Trigger gun discharge allows the user to start and stop foaming with ease
- Trigger gun shuts off automatically if dropped to enhance safety
- Projects rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 10' range)
- Covers up to 500 sq ft (46.5 sq m) in 4 minutes
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- See other Lafferty high water pressure chemical applicators in [Catalog 3](#)

Includes

- Stainless steel mounting bracket
- Stainless steel water inlet check valve
- Machined stainless steel foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose
- Foaming trigger gun, stainless steel wand, fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, SS, Viton, 1/4" # 491324-V

Check Valve, Air, SS, 1/4" MM (Viton / Hast) # 491306

APPLICATIONS

- Food & Beverage
- Animal Health
- Vehicle Wash
- Industrial
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 180°F
Pressure 400 to 1000 PSI
Flow 0.9 GPM @ 700 PSI
Supply Line 1/2"

Compressed Air

up to 3 CFM

Hose

3/8" ID x 50'

Nozzle

40100

Dilution Ratio Range

203:1 to 4:1 @ 700 PSI