

Uni-Body LC Foamer

MODEL # 975555-G

OVERVIEW

The Uni-Body LC Foamer is a medium volume foam applicator (1.3 GPM @ 40 PSI) for projecting foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 12 feet. Gauges display incoming water and air pressure.

Key Features

- The unique machined polypropylene uni-body design is both compact and cost-effective
- Designed for foam cleaning medium to large surfaces
- Creates a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Available with a lower flow rate (#975545-G)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Industrial
- Janitorial/Sanitation
- Metal Processing
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 1.34 GPM @ 40 PSI
Supply Line 1/2"

Compressed Air

up to 3 CFM

Hose

3/4" ID x 40'

Nozzle

50250

Lafferty
EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES

1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com