

MODEL # 975057

OVERVIEW

The Portable 5 Gallon Uni-Body W-50 Spray-All is a water-driven, medium volume spray applicator for applying chemical solutions to a variety of surfaces. Featuring an all stainless steel cart assembly, this venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a uniform spray. With a flow rate of around 2 gallons per minute, this unit is great for spraying virtually any sized area or object quickly and efficiently.



- Creates a medium volume spray
- Designed for spraying medium to large surfaces and objects
- Fan pattern nozzle for even coverage
- Chemical resistant wetted components ensure years of outstanding performance
- Use it anywhere 35-125 PSI water is available
- Available as a wall-mounted unit (#975050)
- See other Lafferty Spray-Alls and more chemical applicators in Catalog 1

Includes

- All stainless steel 2-wheel cart with non-marking tires & integrated hose rack
- Stainless steel, round, 5 gallon jug rack (square available)
- Machined polypropylene injector body
- Inlet and discharge ball valves
- 20 color-coded metering tips for setting dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle



5 Gallon Pail

Pail. 5 Gallon Round W/ Suction Stem # 709105

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Square Jug Rack Conversion

Specify Round or Square Jug Racks at time of order

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 2.3 GPM @ 40 PSI

Supply Line 1/2'

Hose 1/2" ID x 50'

Nozzle 2550

Dilution Ratio Range 526:1 to 7:1 @ 40 PSI











